

- NOTE:
1. DRAWING IS NOT TO SCALE. DIMENSIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.
  2. SUGGESTED MOUNTING HEIGHT OF OUTDOOR UNIT IS 24" MINIMUM FROM ROOF SURFACE TO BOTTOM OF UNIT.
  3. ON OUTDOOR UNITS A LOUVERED VESTIBULE IS ADDED TO THE BURNER AREA. ALL OTHER COMPONENTS HAVE A WEATHERIZED ENCLOSURE.
  4. FLUE VENT, CHIMNEY, AND CAP REQUIRED ON ALL UNITS. (SUPPLIED BY OTHERS)

HORIZONTAL DIMENSIONS FOR INDIRECT FIRED MODELS 150, 175, 200, 225, 250, 275, 300, 350, 400, 450

MODEL	A	B	C	D	E	F	G	H	J	K	L	M	N	FILTERS
1D150/175	100	55	8.5	38	72	90	5	3	42	12	90	5	26	(20) 25 x 20 x 2
1D200/225	116	55	8.5	38	72	100	8	3	55	12	96	10	26	(15) 25 x 20 x 2 (10) 30 x 20 x 2
1D250/275/300	116	60	4.5	51	90	100	8	4	55	14	96	10	36	(15) 30 x 20 x 2 (10) 25 x 20 x 2
1D350/400/450	160	72	8	56	102	150	5	4	60	16	140	10	36	(40) 20 x 20 x 2

