

VERTICAL DIMENSIONS FOR INDIRECT FIRED UNITS
 MODELS 150, 175, 200, 225, 250, 275, 300, 350, 400, 450

MODEL	A	B	C	D	E	F	G	H	J	K	L	M	N
ID150/175	100	55	8.5	38	72	90	5	3	42	12	90	5	26
ID200/225	116	55	8.5	38	72	100	8	3	55	12	96	10	26
ID250/275/300	116	60	4.5	51	90	100	8	4	55	14	96	10	36
ID350/400/450	160	72	8	56	102	150	5	4	60	16	140	10	36

MODEL	FILTER SIZE and QTY.
ID150/175	(20) 25 x 20 x 2
ID200/225	(20) 25 x 20 x 2
ID250/275/300	(18) 25 x 20 x 2
ID350/400/450	(40) 20 x 20 x 2

- NOTE:
- DRAWING IS NOT TO SCALE. DIMENSIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.
 - SUGGESTED MOUNTING HEIGHT OF OUTDOOR UNIT IS 36" MINIMUM FROM ROOF SURFACE TO BOTTOM OF UNIT.
 - ON OUTDOOR UNITS A LOUVERED VESTIBULE IS ADDED TO THE BURNER AREA. ALL OTHER COMPONENTS HAVE A WEATHERIZED ENCLOSURE.
 - FLUE VENT, CHIMNEY, AND CAP REQUIRED ON ALL UNITS. (SUPPLIED BY OTHERS)

