

- NOTE:
1. DRAWING IS NOT TO SCALE. DIMENSIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.
 2. SUGGESTED MOUNTING HEIGHT OF OUTDOOR UNIT IS 24" MINIMUM FROM ROOF SURFACE TO BOTTOM OF UNIT.
 3. ON OUTDOOR UNITS A LOUVERED VESTIBULE IS ADDED TO THE BURNER AREA. ALL OTHER COMPONENTS HAVE A WEATHERIZED ENCLOSURE.
 4. FLUE VENT, CHIMNEY, AND CAP REQUIRED ON ALL UNITS. (SUPPLIED BY OTHERS)

HORIZONTAL DIMENSIONS FOR INDIRECT FIRED MODELS 35, 45, 50, 65, 75, 85, 100, 125

MODEL	A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	FILTER SIZE and QTY.
ID 35/45	60	30	4.25	21.5	90	50	5	1.5	28	6	50	5	21.5	1	38	(6) 20 x 25 x 2
ID 50/65/75	72	28	3.25	21.5	80	58	7	1.5	28	6	58	7	21.5	1	38	(3) 20 x 25 x 2 (4) 16 x 25 x 2
ID 85/100	72	36	5	26	90	58	7	1.5	36	8	58	7	33	1.25	48	(8) 20 x 20 x 2 (8) 16 x 20 x 2
ID 125	85	42	4.50	33	102	76	4.5	1.5	26	10	70	7.5	33	1.5	48	(10) 18 x 20 x 2 (4) 20 x 20 x 2

