

VERTICAL DIMENSIONS FOR INDIRECT FIRED UNITS
 MODELS 35, 45, 50, 65, 75, 85, 95, 100, 125

MODEL	A	B	C	D	E	F	G	H	J	K	L	M	N
ID 35/45	60	30	4.25	21.5	90	50	5	1.5	28	6	50	5	21.5
ID 50/65/75	72	28	3.25	21.5	80	58	7	1.5	28	6	58	7	21.5
ID 85/100	72	36	5	26	90	58	7	1.5	36	8	58	7	33
ID 125	85	42	4.50	33	102	76	4.5	1.5	26	10	70	7.5	33

MODEL	P	FILTER SIZE and QTY.
ID 35/45	1	(6) 20 x 20 x 2
ID 50/65/75	1	(4) 18 x 26 x 2
ID 85/100	1.25	(8) 18 x 20 x 2
ID 125	1.5	(8) 18 x 20 x 2 (4) 20 x 20 x 2

- NOTE:
- DRAWING IS NOT TO SCALE. DIMENSIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.
 - SUGGESTED MOUNTING HEIGHT OF OUTDOOR UNIT IS 36" MINIMUM FROM ROOF SURFACE TO BOTTOM OF UNIT.
 - ON OUTDOOR UNITS A LOUVERED VESTIBULE IS ADDED TO THE BURNER AREA. ALL OTHER COMPONENTS HAVE A WEATHERIZED ENCLOSURE.
 - FLUE VENT, CHIMNEY, AND CAP REQUIRED ON ALL UNITS. (SUPPLIED BY OTHERS)

