METURN AR \\ \\SUPPLY A\\ W\\ 24.000 62.000 36.000 8.000 15.000 33.000 MOTORIZED RETURN AIR DAMPER 18.880 10.500 36.000 -| FRESH AIR T 20.000 -16.188 36" MOUNTING STAND V-BANK FILTER SECTION INLET DAMPER APPROXIMATE GAS CONNECTION LOCATION BURNER HEAT SECTION MOTOR COVER — BLOWER SECTION UNIT MTD. CONTROL MODULE HINGED ACCESS DOOR 72.000 14.250 58.000 33,000 **−** 21.875 **−** 7.00 **7**.000 (2) HINGED - ACCESS DOOR INSPECTION PORT & ACCESS PANEL SPLIT FOR SHIPMENT APPROXIMATE ELECTRICAL CONNECTION LOCATION BEARING COVER LIFTING LUGS

MODEL

AirRite TT Series 218 VTL Outdoor

STANDARD FEATURES

ADJUSTABLE BURNER PROFILE DAMPERS MIDCO BURNER MAXITROL TEMPERATURE CONTROL SYSTEM HEAT & RUST RESISTANT INTERIOR FINISH INDUSTRIAL ENAMEL EXTERIOR FINISH AIR INLET SCREEN (OUTDOOR UNITS ONLY) AIR PROVING SWITCH BELT GUARD (PER OSHA STANDARDS) LUBRICATED BEARINGS W/ ZIRK FITTINGS FACTORY TESTED ELECTRONIC FLAME SUPERVISION UNIT MTD CONTROL MODULE 16 GAUGE CRS CASING (2) 18" DWDI FORWARD CURVED BLOWER TESTED TO ANSI Z83.4 & Z83.18

MOUNTING STAND REQUIRED WHEN INLET DAMPER SELECTED

PRELIMINARY

NOTE:

1.) DRAWING IS NOT TO SCALE.

2.) THIS SUBMITTAL ONLY APPLICABLE TO DIRECT FIRED BURNER.

3.) DUE TO SHIPPING REQUIREMENTS, SOME ELECTRICAL RECONNECTION MAY BE REQUIRED.

WEATHER-RITE