



MODEL	DIMENSIONS									FILTERS
	A	B	C	D	E	F	K	L	M	V-BANK
224	55	110	90	10	20	100	3	35	8	(18) 2x20x20 (12) 2x20x25
230	60	145	115	15	25	135	4	40	5	(6) 2x20x20 (30) 2x20x25

NOTES:

- 1.) DRAWING IS NOT TO SCALE. DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTIFICATION.
- 2.) HH AND HB ARRANGEMENTS ARE STANDARD. CONSULT FACTORY FOR OTHER ARRANGEMENTS.
- 3.) UNITS SHOULD BE INSTALLED AT MINIMUM 24" FROM GROUND.
- 4.) OUTDOOR UNITS ARE PROVIDED WITH WEATHERPROOF HOUSINGS OVER FAN MOTOR, DRIVES AND DAMPER OPERATOR.
- 5.) HB UNITS MAY CARRY OVER MOISTURE, DO NOT INSTALL OVER DAMAGEABLE MATERIALS.
- 6.) INLET SCREEN IS PROVIDED ON OUTDOOR UNITS.
- 7.) ALL UNITS ARE PRE-PIPED, PRE-WIRED, AND FIRE TESTED PRIOR TO SHIPMENT.