

### Remote panel includes:

- Maxitrol series 94 dual temperature selectors for spray and cure
- Fan on / off switch
- Cure / spray mode switch
- Burner on / off switch
- Fan on, cure on, and burner on indicator lights
- Spray mode exhaust fan speed pot
- Cure mode exhaust fan speed pot



### Spray Mode:

1. Start the Bananza supply fan by switching the fan on/off switch to the on position. The inlet damper will begin to open, and the exhaust fan will start. The Bananza supply fan is delayed from starting by a timer to allow the exhaust fan time to ramp up preventing the booth doors from blowing open. The fan on indicator light will illuminate.
2. Adjust the spray mode exhaust fan speed pot to balance the pressure in the booth as needed. To start the burner, switch the burner on/off switch to the on position. When the burner lights, the burner on indicator light will illuminate.
3. Adjust the spray temperature selector to the desired temperature setting. The burner will modulate the discharge air temperature to the setting set on the spray temperature selector dial.

### Cure Mode:

1. If the burner is off, turn the burner on/off switch to the on position. Turn the spray/cure switch to the cure position. Once the burner is on, use the cure mode exhaust fan speed pot to balance the air in the booth.

### Shut down:

Turn the burner on/off switch to the off position. Turn the fan on/off switch to the off position